

3COM GIGABIT SWITCH 5 AND SWITCH 8

Compact, streamlined and affordable highspeed switching with autosensing and auto MDI/MDIX for easy operation



from top: 3Com Gigabit Switch 8, Gigabit Switch 5

OVERVIEW

The 3Com® Gigabit Switch, available in 5 and 8 port versions, is designed for small offices requiring high network performance to exchange large data files and images and access real-time information. Featuring autosensing and auto MDI/MDIX on all ports, these Gigabit switches are delivered in compact streamlined enclosures, the 3Com logo illuminates on power up, and blue LEDs indicate port connections.

The 3Com Gigabit Switch 5 and 8 automatically find the fastest connection speed; all that is needed is to connect the power and Ethernet cables. There is no software to configure. Easy to set up, these switches feature a fan-less design which provides silent operation. With a choice of five or eight ports you can expand your network by adding more computers or devices with speeds up to 2000 Mbps per port in full-duplex mode. The Gigabit Switch 5 and Switch 8 also provide jumbo frame support.

These switches offer high-speed, high-quality, reliable, affordable networking with a style that will accommodate any office environment and is backed by an outstanding 2-year limited warranty.

KEY BENEFITS

OPTIMAL NETWORK CONNECTIVITY

Auto-speed sensing enables connection at 10, 100 and 1000 Mbps, ensuring optimum throughput while retaining compatibility with legacy equipment.

IEEE 802.1p Quality of Service (QoS) traffic prioritization helps ensure that critical time-sensitive traffic like voice gets the priority needed for quality communications.

Full-duplex support of your network allows full, two-way data transfer, doubling the effective bandwidth.

FCC Class B certification for home and office use (is more stringent than Class A certification).

EASY TO USE

Auto MDI/MDIX eliminates most common cabling problems, whether the port is connected to a server, PC, another switch or hub.

Front panel LEDs provide immediate notification of network use without requiring special technical knowledge.

Operating system independence allows for maximum integration of different operating systems within a network—no extra configuration of the network is required.

Plug-and-Play convenience delivers simple set-up; no complicated configuration is required.

Silent operation. No-fan design ensures there is no noise disturbance from the switches.


RELIABLE

2-Year limited warranty provides the on-going warranty support that businesses need.



3COM

Typical Network Configuration



SPECIFICATIONS

All information in this section is relevant to all members of the 3Com Gigabit Switch family, unless otherwise stated.

CONNECTORS

All ports are auto MDI/MDIX, auto-negotiating RJ-45

3Com Gigabit Switch 5

5 10BASE-T/100BASE-TX/1000BASE-T

3Com Gigabit Switch 8

8 10BASE-T/100BASE-TX/1000BASE-T

REGULATORY AND AGENCY APPROVALS

Safety: UL 60950-1, EN 60950-1, CSA 22.2 60950-1, IEC 60950-1

EMC Emissions: FCC Part 15 Subpart B Class B, ICES-003 Class B, EN 55022 Class B, CISPR 22 Class B, EN 61000-3-2, EN 61000-3-3

EMC Immunity: EN 55024

ENVIRONMENTAL SPECIFICATIONS

Operating temperature: 0° to 40°C (32° to 105°F)

Operating humidity: 10% to 90% (non-condensing humidity)

DIMENSIONS

Gigabit Switch 5

Width: 117.0 mm (4.6 in)

Height: 30.5 mm (1.2 in)

Depth: 92.0 mm (3.6 in)

Weight: 180.0 g (6.3 oz)

Gigabit Switch 8

Width: 157.58 mm (6.2 in)

Height: 30.5 mm (1.2 in)

Depth: 91.4 mm (3.6 in)

Weight: 240.0 g (8.5 oz)

POWER SUPPLY

External power supply

Input voltage: 100-240 VAC, 50/60 Hz

Power consumption:

Gigabit Switch 5 – 3.4W

Gigabit Switch 8 – 4.0W

Standards Compliance

IEEE 802.1p Priority Tags

IEEE 802.3ab Gigabit Ethernet

IEEE 802.3i 10BASE-T Ethernet

IEEE 802.3u 100BASE-TX Fast Ethernet

IEEE 802.3x Flow Control

Jumbo frames

PACKAGE CONTENTS

Switch, power adapter, self-adhesive rubber pads, installation guide, Support and Safety information sheet, warranty flyer

Warranty and other services

Two Year Limited Hardware Warranty

Limited Software Warranty for 90 days

30 days of telephone technical support

Refer to www.3com.com/warranty for details.

SERVICE AND SUPPORT

3Com Global Services offers the resources and talents of a major corporation plus more than two decades of experience in resolving network challenges and delivering business benefits to enterprises around the world.

Global support with a personalized, local focus in the local language helps drive productivity and minimize expenses. Because 3Com understands both the technology and the business, we're the partner you need to remain strong and competitive.

ORDERING INFORMATION

PRODUCT DESCRIPTION

3Com Gigabit Switch 5

3Com Gigabit Switch 8

3COM SKU

3CGSU05A

3CGSU08A

Visit www.3com.com for more information about 3Com solutions.

3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064
3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2010 3Com and the 3Com logo are registered trademarks in various countries worldwide of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice.

401000-006 01/10

